

# SAFE AND RELIABLE OPERATION

An amber light is used to represent a high level alarm and red lights annunciate an overfill warning. Additionally, an alternating 105 decibel tone indicates a high level alarm while a steady 105 decibel tone signal indicates an overfill warning. The audible signals can be easily heard from any location on the deck.

## **COST EFFECTIVE**

APM-2E is a cost effective option to APM-2 to provide fixed mounted barge high level and overfill occurrence notifications when there is not a need to have individual tank identification.

### **SOLAR POWERED**

APM-2E comes with a solar panel charging to maintain battery power.

## **ALARM PANEL BYPASS**

The panel comes with a Bypass switch if there is a need to bypass the panel.

### **TANDEM LOADING**

An optional single/tandem loading switch is available to allow for Tandem Loading Capability.

LOW BATTERY POWER WARNING The panel is equipped with a low battery warning light and cycles the alarm horn which requires a manual reset to clear.

# **COMPLETE PACKAGE**

APM-2E comes with solar panel mounted directly to the cabinet. All that is needed is to mount the cabinet and connect power to the remote battery box.



# APM ALARM PANEL HIGH LEVEL AND OVERFILL PROTECTION FEATURES AND OPTIONS

	APM-3	APM-1B LITE	APM-1TLB	APM-2E/F	HIGH LEVEL OVERFILL  WITH THE PROPERTY OF THE
Mounting	PORTABLE	PORTABLE	PORTABLE	FIXED	FIXED
Testing Capability	•	•	•	•	•
Loading Capability		•	•	•	•
Tandem Loading Capability			•	•	•
High Level and Overfill Occurance Detection	•	•	•	•	•
Individual Cargo Tank Notification					•
Bypass Option Available				•	•
Solar Powered Battery Recharging				•	•
120V Charging Connection			•		
Weight (lbs.)	8	18	34	47	89